



611 Argyle St. N. Caledonia, Ontario N3W 1M1

TEL: (800) 655-3447

FAX: (800) 955-4991

Email: [sales@acsvalves.com](mailto:sales@acsvalves.com)

Website: [www.acsvalves.com](http://www.acsvalves.com)



## FT (Flex-Tip) Rotary Valve

### Features

---

- Available in 10 sizes
- Designed for 18" WG
- Fabricated mild steel construction
- EPDM standard wipers which have good abrasion resistant characteristics
- Dual or single rotor wiper blades
- 4-bolt normal duty flange bearings
- Standard right angle gearmotor with chain drive
- PSHA guarded
- Standard temperature up to 300 ° F
- Removable side plate for easy maintenance

### Options

---

- Reduced volume rotor pockets
- Stainless Steel construction
- Optional polyurethane wiper material available
- Customs sizes available
- Motion speed switch
- Special motors available
- Direct drive motor available
- Horizontal drive configurations avail
- Standard or extended clearance wipers



611 Argyle St. N. Caledonia, Ontario N3W 1M1

TEL: (800) 655-3447

FAX: (800) 955-4991

Email: [sales@acsvalves.com](mailto:sales@acsvalves.com)

Website: [www.acsvalves.com](http://www.acsvalves.com)

FT Flex Tip Rotary Valve Capacity Chart	
SIZE	C.F.R.
4"	.10
6"	.23
8"	.64
10"	1.34
12"	2.46
14"	6.2
16"	6.2
20"	12.6
24"	21.0
30"	42.4